

Custom Hydraulic Center Hole Cylinders - Single & Double Acting

Model	Capcty (Tons)	Stroke (Inch)	Area (In ²)	Weight (Lbs)	Dimensions (Ins)			
					Diameter	Height	Rod Diameter	Hole Diameter
WB2006DCG	200	6	39.85	275	10.75	14.00	7.50	4.13
WB2008DCD	200	8	40.45	311	10.81	16.13	7.50	4.00
WB20012DCTK	200	12	49.30	500	12.00	23.25	8.00	4.13
WB20012DCR1	200	12	49.30	578	12.12	22.12	6.87	4.00
WB2003DCR	246	3	49.30	344	12.00	14.90	8.00	4.00
WB2006DCTK	246	6	49.30	385	12.00	16.25	8.00	4.13
WB20012DCR2	246	12	49.23	650	12.00	23.25	8.00	4.13
WB20012DCR3	246	12	49.23	630	12.00	23.25	6.87	4.00
WB2506DCR	297	6	59.49	516	13.00	18.00	8.00	4.50
WB3008DCP	300	8	64.90	670	13.30	17.03	7.70	4.06
WB30010DCR	300	10	68.19	700	13.00	19.50	8.00	4.00
WB3006DCR	314	6	78.54	714	15.00	18.50	9.90	5.00
WB3006DCG	392	6	78.54	714	15.00	18.50	9.90	5.50
WB4008DCPA	400	8	88.63	716	15.75	16.34	11.03	5.90
WB4008DCPB	400	8	81.44	523	16.00	17.50	10.00	5.90
WB40012DCR	400	12	113.20	1300	17.25	26.00	12.50	5.88
WB5006DCR	500	6	103.67	935	16.88	18.50	10.50	5.50
WB50012DCR	500	12	118.15	1200	16.88	28.41	12.00	5.50
WB50012DCP	500	12	103.67	1250	16.88	24.50	10.50	6.00
WB60012DCTK	635	12	127.10	1663	19.50	23.70	9.80	5.90
WB6006DCTK	646	6	129.30	1500	17.75	21.75	12.00	5.25
WB6008DCTK	646	8	129.30	1600	17.75	23.50	12.00	5.25
WB1400DC	1400	14	337.35	5000	31.00	35.00	19.00	12.00